



Request for Quotation

Cootamundra-Gundagai Regional Council is seeking quotations for Tipper Truck and Dog Trailer as described in the below specification.

Instructions: the Respondent must complete all relevant sections. Failure to sign statement below by authorised representative will render bid invalid. Respondents are cautioned to carefully read any and all instructions and the terms and conditions on any of the attached sheets.

Failure to adhere to these instructions and terms and conditions may result in rejection of the bid.

RFQ Title **Tipper Truck Dog Trailer**

RFQ Number **RFQ2025/2**

Issue Date **05/08/2024**

RFQ Closing Time and Lodgement Details	
RFQ Closing Date:	Monday 26/08/2024
RFQ Closing Time:	2pm
RFQ Lodgement Instructions:	All responses must be lodged via Vendor Panel and include completed forms as per pages 4-12 of this document

Council Contact & Enquiries

Name: Thomas Brooke or **Phone:** 0438645745

Email : Thomas.brooke@cgrc.nsw.gov.au

Cc : Graeme.braun@cgrc.nsw.gov.au

RFQ Instructions – All Quotations are subject to the following requirements where indicated

- Quotations are to conform with the Specification
- All attachments must be completed and returned from page 4-12
- Quotations must detail manufacturer's name and model number of each item offered
- Quotations must provide detailed manufacture specifications and complete descriptive literature on each item offered
- Responses **MUST** be submitted in **one** PDF document only

Delivery and registration

1. The price submitted will include delivery to Cootamundra-Gundagai Regional Council's Depot, at 48 William Street Gundagai and include the provision of the vehicles first scheduled service. All vehicles are to arrive with NSW registration for a period of 12 months and include registration paperwork to demonstrate appropriate registration.
2. Reimbursement of the cost of registration will be made separately; therefore the cost of registration should be invoiced independently.
3. Council will supply the Compulsory Third Party Insurance and the registration letter of authority to the successful supplier.

Transport for NSW – Requirements

All vehicles must meet all Transport for NSW requirements. Any manufactured equipment i.e. modifications must be fitted with the necessary engineers compliance plates.

Safework – Requirements

1. Council's operators and at least one of Councils maintenance staff are to be trained in the safe operating procedures of the vehicle/s and all their associated equipment. This training must occur at the date and time of delivery and be scheduled at least 2 business days before delivery.
2. The training will also include, but not be limited to, pre-start checks and daily maintenance.
3. A complete risk assessment for the vehicle/s is to be completed and provided to Council upon delivery. The risk assessment is to be incorporated into the training.

Warranty

Details of all warranties are to be submitted with response. All terms and conditions must be clearly stated and include details of any non-genuine equipment fitted along with any extended warranty that may be available.

Manuals

All vehicles shall be supplied with the following manuals on delivery:

1. One workshop manual, complete with electronic, engine and transmission details including systems operation and disassembly and assembly in PDF format.
2. One spare parts manual in PDF format.
3. Two operators manuals. One must be in hard copy and one must be in PDF format.

Delivery

The anticipated delivery timeframe is to be clearly shown in the response.

Australian Content

The response should clearly set out what (if any) Australian manufactured components are to be included in the tipper truck and dog trailer offered.

Quotation Evaluation

Council will seek to obtain best value for money in any purchasing activity. Council will consider a minimum of the following when evaluating quotations:

- Price
- Operational costs
- Product quality
- Ongoing product support
- Supply and delivery timeframe of quoted items as well as spare parts
- Work health and safety benefits and risks

Trade-in

Council is offering the following vehicles for trade-in as described below:

2015 Hino 700 series bogie tipper

Rego:CF95AA

Chries Body Builders tipping body,

Approx 330,000km. CED 1 October 2024

3 Axle dog trailer. Chries Body Builders topping body built 2015.

The vehicle and trailer can be inspected on request.

The trade in vehicle will not be released to the vendor prior to delivery of new vehicle.

Detail to Include in Quotation

Price (specify lump sum or per unit & include GST)

Discounts/Incentives

Product availability and delivery Conditions

Any other relevant details/conditions relating to the supply of goods

Warranties/Guarantees offered on goods



Specification

Council is seeking quotations on Tipper Truck Dog Trailer as described below.

Please complete and return the following five (6) pages with your response.

Item no	SPECIFICATIONS – TRUCK	Tick
1.	Diesel Engine with a minimum power rating of 500 hp.	
2.	Dual element air cleaner filtration system. Preferably with snorkel .	
3.	Minimum 12 speed manual transmission with synchromesh gearbox or 12 speed automatic gearbox , Council would prefer an automatic gearbox if available. Specify _____	
4.	GVM - 27,000kg minimum GCM - 70,000kg minimum Specify - Tare _____ GVM _____ GCM _____	
5.	Compliance plate shall be current model. Specify build date _____	
6.	Rear air bag suspension, minimum 4 air bags, 17 tonne minimum capacity, air dump switch in cab. Rear axle capacity 17 tonne minimum. Front axle capacity 6.0 tonne minimum	
7.	Heavy duty rear differentials with power divider and locking center differential.	
8.	Fuel tank capacity minimum 400 litres. Specify _____ Tank to have lockable filler cap or other suitable anti syphon protection. Tank to be clearly labelled as Diesel Tank to be clearly labelled as Ad-Blu (if fitted)	
9.	Disc brakes preferred. Engine braking. Truck braking system to comply with ADR35. Braking system must be suitable to allow safe towing of dog trailers being offered in this specification document. Automatic adjusting brakes - Yes / No. Disc Brakes - Yes / No	

10.	Bullbar	
11.	Vehicle stability control	
12.	Heavy duty lockable toolbox large enough to carry jack, wheel brace, grease gun and tools.	
13.	Hand wash tank & soap dispenser	
14.	Ring feeder tow hitch with all necessary air, electric, hydraulic couplings and trailer brake controls . This setup must be organized for easy and safe access for operator to connect & disconnect hoses and airlines . Hinged rubber protection flap over ring feeder	
15.	Mudflaps fitted front & rear of all axle groups. Hinged rear mudflaps with chains to prevent folding back onto tyres	
16.	All terrain tyres suitable for sealed & unsealed roads. Spare tyre & rim to be supplied with same tyre type as the drive tyres. Spare tyre to be mounted in a position where it can safely & easily accessed by one person. All wheels nuts are to be fitted with tension indicators, Jack & wheel brace shall be suitable for both truck and trailer.	
17.	Air dryer fitted to full air system & automatic air tank drain valves shall be fitted to all air tanks.	
18.	Truck to be white in colour. Forward control extra cab (eg room behind seats for eskys ,drivers day comforts) Total length of truck and tipper body not to exceed 8 metres. Cabin & body to be signed with TARE, GVM, GCM	
19.	Heavy duty batteries with isolation switch & vandal proof protection	
20.	Two LED amber rotating beacons must be mounted on the cab so they are clearly visible in normal daylight at a distance of 200m in all directions. Beacons must be able to be switched on and off from inside the cab with an illuminated switch which is clearly labelled. LED tail lights, numberplate light and side clearance lights shall be installed. Tail lights shall have rock protection	
21.	Bluetooth <i>Right Weigh</i> (or equivalent) load scales are to be fitted to trucks & trailers.	

22.	Air suspension driver seat with lumbar support. Heavy duty canvas seat covers shall be fitted to all seating positions. Heavy duty rubber floor mats shall be fitted for all seating positions.	
23.	Air conditioned cabin, Tinted windows, Laminated windscreen shall be included. Windscreen stone guard to protect lower half of windscreen Driver side weather shield shall be fitted.	
24.	1 x 9kg dry powder fire extinguisher is to be fitted outside the cab, preferably in a red plastic box (jonescoplastic.com) and be accessible from ground level.	
25.	Power steering, cruise control, central locking, electronic windows, AM/FM radio with bluetooth capability, 2 x 12 volt accessory charging ports suitable for mobile phones, tablet etc shall be fitted. Voltage reducer to be fitted if necessary for charging ports & radios to ensure that a 12volt power supply is available. ACMA approved UHF to be fitted by supplier with handpiece to be mounted where they are easily accessible by the driver. The UHF shall be wired to the ignition switch.	
26.	All standard gauges including fuel, oil, temperature, speedo, air pressure, revs, engine hours etc. Specify any non-standard items included _____	
27.	Electronic adjustable & heated mirrors with independently adjustable spotter mirrors.	
28.	Reverse camera	
29.	Induction training for operators and workshop to be supplied on delivery. All control switches are to be clearly labelled i.e. tipper, beacons, etc	
30.	Three complete sets of keys including fuel cap keys shall be supplied at delivery.	
31.	Plant Risk Assessment. The successful supplier shall provide a comprehensive plant risk assessment for the plant being purchased prior to invoicing. Council uses the Plant Assessor plant risk assessment system and would prefer suppliers to provide risk assessments in Plant Assessor format. Plant is to be supplied compliant with the risk assessment with all labels fitted. Plant Assessor can be contacted on 1300 728 852 or at www.assessor.com.au ”	

32.	<p>Full set of service filters (oil air, fuel, cabin, hydraulic, adblue, etc) to be supplied.</p> <p>Detailed list of service part numbers (filters) and oil types/grades to be supplied.</p> <p>Sample Kits if necessary.</p>	
------------	--	--

Item no	SPECIFICATIONS – TIPPER (FOR TRUCK)	Tick
1.	<p>10m3 high tensile steel (Bisaloy) tipping body, painted white, with the following minimum specifications:-</p> <ul style="list-style-type: none"> • Floor, fixed sides, front & tailgate to be 5mm thick • Tipping body to be ribless • Fixed side height to be approx. 1150mm high • Dual swing tailgate with side swing opening to kerb side. • Air operated tailgate release with 4 locking lugs. Manual lock handle on RHS of tipper with safety lock ring • Heavy duty spreader chains to control tailgate under tipping conditions • Rope rails running full length both sides and tailgate • One shovel rack to be fitted to headboard on tipper. • Fold down ladder & access steps with 3 points of contact to be positioned on both sides of tipper body to allow access without interference from the tarp. • Tipper safety prop capable of holding body independent of hydraulics. Must be able to be put in place by 1 person without person having to go in between truck chassis and tipper body. • Rear marker signs to comply with Transport for NSW requirements • Body to be constructed & fitted to distribute load legally over each axle <p>Tray Specify: Length _____mm Width _____mm</p>	
2.	<p>Retractable tarp system, electronically operated from inside the cabin. Remote shall include a dock to store within cabin if supplied.</p> <p>Tarp system has to be of good quality with replacement parts easily accessible from supplier.</p>	
3.	<p>25 tonne hydraulic hoist designed to give 48 degree tipping angle when fully raised. Hoist to be fully protected from load material and have inspection holes at the front for the top pin. Hoist to be greaseable from ground level.</p>	
4.	<p>Minimum 50mm rear pivot bar with 4 x 80mm mounting bushes on the body and 2 x 80mm bushes on the sub frame. All to be greaseable</p>	

5.	Hydraulic oil tank to be metal and capacity to suit operational requirements. Ball valve tap to be fitted at the bottom to allow the tank to be drained easily. All hydraulic hoses are to have anti burst valves. Tank is to be clearly labelled and include a gauge to show oil level. Tank filler cap to be on opposite side of tank feeder and have a baffle to prevent overflow from the filler cap.	
6.	PTO to be directly mounted to the transmission.	
7.	Tipper hoist control to be positioned so it is easily accessible from the driving position and to be clearly labelled with operating instructions.	

Item no	SPECIFICATIONS – 3 AXLE SUPER DOG TRAILER	Tick
1.	<p>14-15m³ high tensile steel (BISALOY) tipping body, painted white, with the following minimum specifications:-</p> <ul style="list-style-type: none"> • Turntable dolly lock • Dual swing tailgate with side swing opening to kerb side. • Floor, fixed sides, front & tailgate to be 5mm thick • Tipping body to be ribless • Fixed side height to be approx. 1150mm high • Dual swing tailgate with side swing opening to kerb side. • Air operated tailgate release with 4 locking lugs. Manual lock handle on RHS of tipper with safety lock ring • Heavy duty spreader chains to control tailgate under tipping conditions • Rope rails running full length both sides and tailgate • One shovel rack to be fitted to headboard on tipper. • Fold down ladder & access steps with 3 points of contact to be positioned on both sides of tipper body to allow access without interference from the tarp. • Tipper safety prop capable of holding body independent of hydraulics. Must be able to be put in place by 1 person without person having to go in between truck chassis and tipper body. • Rear marker signs to comply with Transport for NSW requirements • Body to be constructed & fitted to distribute load legally over each axle • Protection of hoses/cablings/ airlines along A frame tow bar. <p>Tray Specify: Length _____mm Width _____mm</p>	
2.	Rubber hinged “A” frame drawbar with ring feeder eye & all fittings to match truck specified above. Drawbar to be spring assisted, constructed to eliminate load material from building up on the frame and have a cover. All electrics and air lines to be run in a steel protective cover. Spare tyre to be mounted on the “A” frame.	
3.		

	30 tonne hydraulic hoist designed to give 48 degree tipping angle when fully raised. Hoist to be fully protected from load material and have inspection holes at the front for the top pin. Hoist to be greaseable from ground level. Hydraulic hoses to have anti burst valves.	
4.	Minimum 50mm rear pivot bar with 4 x 80mm mounting bushes on the body and 2 x 80mm bushes on the sub frame. All to be greaseable	
5.	Trailers to be PBS compliant (www.nhvr.gov.au/road-access/performance-based-standards)	
6.	Retractable tarp system, electronically operated from inside the cabin . Remote if supplied	
7.	LED tail lights, numberplate light and side clearance lights shall be installed. Tail lights shall have rock protection	
8.	Mudflaps fitted front & rear of all axle groups. Rear mudflaps to run entire width of tipping body	
9.	Air bag suspension with height control valves located in a protected area.	
10.	Tipper hoist control to be positioned so it is easily accessible from the driving position and to be clearly labelled with operating instructions.	
11.	Brake system to comply with ADR38/04, including <ul style="list-style-type: none"> • Disc brakes/ Drum • Air tanks with manual drains including cables • ABS brakes on all axles 	

Bidder Information	
Company Name	
ABN	
Business Address	
City / Town	
State	
Post Code	
Office Phone	
Office Fax	
Email Address	
Website	
Respondents contact details	
Name	
Mobile Phone	
Office Phone	
Email Address	

Bid Statement

"I certify that this bid is made without prior understanding, agreement or connection with any corporation, firm or person submitting a bid for the same materials, supplies, or equipment, and is in all respect fair and without collusion or fraud. I agree to abide by all conditions of this bid and certify that I am authorised to sign this bid for the bidder."

Respondents Authorised Representative Name:	
Date:	
Quotation total (including GST):	
Authorised representatives signature:	

Quotation form – Tipper Truck Dog Trailer

Make	
Model	
Year of Manufacture	

All prices shall include GST	
1x Tipper Truck	\$
1X 3 AXLE SUPER DOG TRAILER	\$
Trade-in price:	\$
Price firm for	6 weeks

Delivery time from date of order:	
--	--

Warranty	
Engine make and model	
Engine capacity	
Engine power	
Engine Torque	
No. of cylinders	
ADR compliant level	
Gearbox :Manual/Auto / Type .	
No of speeds:	
Power Flywheel (SAE Net) No of cylinders:	
_____ KW @ _____ RPM	

Tyre sizes and Ply rating:	
DIFFERENTIALS -	
Axles:	
Capacity:	
SUSPENSION -	
Front:	
Rear:	
Australian Content %	

Customer References (quoted model only)			
Owner	No. Owned	Contact name	Contact number

